

NOTE:
 1. SOLDER TALL TO BE WITHIN 0.05 UPWARD AND 0.15 DOWNWARD FROM Z-DATUM PLACE, AND COPLANARITY OF SOLDER TAILS TO BE WITHIN 0.10 MEASUREMENT POINT SOLDER TAILS TIP

1. INSPECTION SYMBOL:

- : MANUFACTURER INSPECTION
- ◆ : Q.C INSPECTION

2. MATERIAL:

MOLDING: THERMOPLASTIC, COLOR: BLACK, UL-94V0
 SHELL: COPPER ALLOY, T=0.35 MM
 TERMINAL: COPPER ALLOY, T=0.15 MM



3. FINISH:

CONTACT: GOLD PLATE ON MATING SURFACE,
 ALL OVER NICKEL UNDER PLATE
 SHELL: GOLD PLATE ON THE POST
 ALL OVER NICKEL UNDER PLATE

4. HSF: HSF CONCRAFT LEVEL 1

128AA19CB□N

- A=3u"Au 焊脚镀金
- B=10u"Au 焊脚镀金
- C=15u"Au 焊脚镀金
- D=30u"Au 焊脚镀金

				GENERAL TOLERANCE		DRAW:	PART NO: 128AA19CB□N
C	E130580A	Cookie	12/10/2013	X. ±0.30	X° ±2.00°	CHECKED:	TITLE: HDMI 19PIN SMT
				.X ±0.20	.X° ±1.00°		
				.XX ±0.10	.XX° ±0.50°		
B	E110234A	Marcy	06/16/2011	.XXX ±0.05		APPROVE:	DRAWING NO: 128AA19CB□N
A	E090359A	Caven	11/26/2009	UNITS: mm	DATE: 12/10/2013		
REV.	ECO NO.	DRAW	DATE				
MATERIAL:	FINISH:	SCALE: 2.5 : 1	SHEET: 1 / 1	REV. C			