



P/N LEGEND

A2506 H-XP XXX			
①	②	③	④
① Series No.			
② Connector type: H=Housing			
③ No. of circuits			
④ Option code:			
Blank=Nylon66-V0, Beige(7506C)			
-WH=Nylon66-V0, White			
-BK=Nylon66-V0, Black			
-BL=Nylon66-V0, Blue(280C)			
-RD=Nylon66-V0, Red(1785C)			
-RD2=Nylon66-V2, Red(186C)			
-NF=PA66,UL94V-2 NO FLAME, Beige			

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1000V AC/minute

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.50	5.80	10P	22.50	25.80
03P	5.00	8.30	11P	25.00	28.30
04P	7.50	10.80	12P	27.50	30.80
05P	10.00	13.30	13P	30.00	33.30
06P	12.50	15.80	14P	32.50	35.80
07P	15.00	18.30	15P	35.00	38.30
08P	17.50	20.80	16P	37.50	40.80
09P	20.00	23.30			

JOINT TECH ELECTRONIC IND. CO., LTD.			
UNIT	SCALE	SHEET	TITLE: 2.50mm PITCH HOUSING
mm	1 : 1	1 of 1	
DRAWN BY 董正一 2001.02.01	APPROVED BY 董正一 2001.02.01		
GENERAL TOLERANCE			
B3	EN1507130001	2015.07.29	周傑亮
B2	EN1012020284	2010.12.03	陳錦展
REV.	DESCRIPTION	DATE	NAME
			X. X±0.25
			X. XX±0.15
			X. XXX±0.05
			ANGLE±
			DRAW NO. : A2506H-XP
			REV. B3