





宏聚电子五金制品有限公司




HONGJU ELECTRONIC & METAL PRODUCTS CO.,LTD

R


受控文件



Rating: 16A 125/250VAC (UL CUL)
 16(4)A 250V AC (VDE ENEC CB CQC)
 Contact Resistance: 50m Ω (Max)
 Insulation Resistance: DC 500V 100M Ω (Min)
 Dielectric Strength: AC1500V 1 minute
 Electrical life: 10,000 cycles
 Operating Temperature: 0℃~85℃¹⁰
 Safety Approval:



	X	Y
1	30.0+0.1	22.0+0.1
2	30.2+0.1	22.0+0.1
3	30.4+0.1	22.0+0.1



MATERIAL:

Body:Nylon66, UL rated:94V-2 min
 Actuator:Nylon66, UL rated:94V-2 min
 Terminal:Brass,silver or tin plated

Marking	X	0	1	2	3	4	5	7	8	9	B	C	E	F	G
柄	None														

公差	版本	比例尺	角度	单位	品名	图号
TOLEANCES	VERSION	SCALE	ANGLE	UNIT	TITLE	DRAWING NO
.X± 0.3	A1	NONE	± 1°	mm.	R-210-CXN-BB	R-210-CXN-BB_A1
重新整理发行	2009.09.17	N/A	2008.04.16	黄雄阳		
首版发行	2008.04.16	N/A		李伟奇		
变更说明	日期	ECN NO.	APPROVED BY	李新堤	李伟奇	
版本 VER.	日期 DATE	ECN NO.	APPROVED BY	李新堤	李伟奇	

File Code: HJ-WI-E-03A