



- Specification:**
- 1. Electrical Characteristics:**  
Dielectric Withstanding Voltage: AC 500V/1MINUTE.  
Insulation Resistance: 1000 MΩ/Min.  
Contact Resistance: 30 mΩ Max.
  - 2. Mechanical Characteristics:**  
INSERTION FORCE: 30N(3.06kgf) MAX  
EXTRACTION FORCE: 10~30N(1.02~3.06Kgf)  
Durability: 1500cycles, EXTRACTION FORCE: 10~30N(1.02~3.06Kgf)
  - 3. Material:**  
Terminal: Phosphor Bronze, C5191/C2680R-EH T=0.25  
Plating: Gold 0.76 um Min plating over 1.27 um Min Nickel underplate, 2.54 um Min Sn selective plating on solder tail;  
Shell: Bronze, C2680R-H=0.30mm  
Plating: Nickel underplate 2.54 um Min;  
Housing: LCP Black
  - 4. Environmental:**  
Operating Temperature: 0°C to +85°C.

产品图

深圳市精拓金电子有限公司

公差一览表		制图		制图料号	
TOLERANCE UNLESS OTHERWISE	UNIT	DRAWING	Z-Y-B	PRODUCT PART NO.	
X ±0.25	X	MM		产品名称	USB A/F 苹果SMT短体四脚 (大办弹片)
X ±0.20	X	SCALE	1:1	PRODUCT NO.	
XX ±0.15	XX	DATE	2013.10.24	角法	
XXX ±0.05	XXX	APPRO	审核	版本	AD
				VER	

MAPX	MODIFICATION	DATE
------	--------------	------