


NPN General Purpose Amplifier



Features

- Epoxy meets UL-94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking:

S8050-L J3Y • L
S8050-H J3Y

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	VCBO	V		40
Collector-Emitter Voltage	VCEO	V		25
Emitter-Base Voltage	VEBO	V		5
Collector Current -Continuous	IC	mA		500
Total Device Dissipation	PD	mW		300
Junction Temperature	TJ	°C		150
Storage Temperature	TSTG	°C		-55 to +150

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	IC=100uA,IE=0	40		
Collector-emitter breakdown voltage	$V_{(BR)CEO^*}$	V	IC =100uA,IB=0	25		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	IE=100μA,IC=0	5		
Collector cut-off current	I_{CEX}	nA	VCE=20V, IB =0			100
Base cut-off current	I_{CBO}	nA	VCB=40V, IE=0			100
Emitter cut-off current	I_{EBO}	nA	VEB=5V, IC =0			100
DC current gain	$h_{FE(1)}$		VCE=1V,IC=50mA	120		350
	$h_{FE(2)}$		VCE=1V,IC=500mA	50		
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=500mA,IB=50mA			0.6
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=500mA,IB=50mA			1.2
Transition frequency	f_T	MHz	VCE=6V,IC=20mA,f=30MHz	150		







■ Classification Of Hfe (1)

Rank	L	H
Range	120-200	200-350

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S8050	F2	Approximate 0.008	3000	30000	120000	7" reel





■ Characteristics (Typical)





S8050-L THRU S8050-H

RoHS
COMPLIANT







S8050-L THRU S8050-H


RoHS
COMPLIANT

■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.