

SPECIFICATIONS

Rated(额定参数): 300V,1.5A
 Dielectric strength(抗电强度): AC2000V/1 Minute
 Insulation Resistance(绝缘电阻):1000MΩ Min
 Contact Resistance(接触电阻):20mΩ Max
 Temp. range(操作温度): -40℃~+105℃
 MAX Soldering(瞬时温度):+250℃,5s

Housing Material(塑件): PA66 (UL94 V-0)
 Contact(端子): Brass, Tin plating(黄铜镀锡)

	PITCH RANGE		NOMINAL DIMENSION RANGE							
	IN MM		IN MM							
TO	6	OVER	10	OVER	30	OVER	60	OVER	100	OVER
	10	TO	24	TO	30	TO	60	TO	100	TO
±0.10	±0.15	±0.25	±0.30	±0.30	±0.50	±0.70	±1.00			

Ordering Information

JL2EDGV-XXX XX G X 1





Pitch
 500=5.00PH
 508=5.08PH

No.of pins
 2P~24P

Housing Color
 B=Black
 G=Green
 U=Blue
 R=Red
 W=White
 Y=Yellow
 O=Orange
 E=Grey

Packing
 O=Pe bog
 A=Troy
 T=Tube

Recommended P.C.B Layout(Top Side)



OPERATION		DRAW		BEN		SCALE		FIT		PART NO.	
XX	±0.30				17.01.05	UNIT	mm	A4	1/1	JL2EDGV-XXXXXXG1	
X:XX	±0.20	CHECK				SIZE				5.00/5.08mm Pitch Male Plugable Terminal Blocks	
X:XXX	±0.10					SHEET					
Angle	±3'	APPROVE				PROU.					
DIM	TOL									TITLE:	
CHANGE										5.00/5.08mm Pitch Male Plugable Terminal Blocks	
MODIFICATION DESCRIPTION										PART NO. JL2EDGV-XXXXXXG1	
NEW DRAWING										5.00/5.08mm Pitch Male Plugable Terminal Blocks	
DATE										TITLE:	
REV										5.00/5.08mm Pitch Male Plugable Terminal Blocks	

JILIN 深圳市锦凌电子有限公司
 SHENZHEN JINLING ELECTRONIC CO.,LTD
 Tel: 86-755-2997-5806/5802 Fax: 86-755-2997-5992