

Approval Sheet for Product Specification

承认书

PRODUCT NAME	【产品名称】：	speaker
CUSTOMER PART NO	【客户型号】：	
QINGLONG PART NO	【我司型号】：	MP36M08
DESCRIPTION	【规格】：	8 Ω 0.5W
CUSTOMERS	【客户名称】：	QE-1307

【注意/note】

1. This product shall comply with RoHs. 上本品符合欧洲RoHs规定指令.
2. IN CASE OF CHANGES, SUCH AS DIE &MOLD, MANUFACTURING PROCESS, MATERIAL, APPEARANCE, AND INSPECITION etc., THE SAME PROCEDURE IS REQUIRED. 此部品确认后. 如模具、制造方法、材料、外观、检查等发生变更的情况下必须事前由双方讲行合议。

APPROVAL SEAL (承认印):

DISCUSS		RESOLUTION		
QA	PURCHASE	ISSUED	CHECKED	APPROVED
		BY	BY	BY

型号 Model	MP36M08
尺寸 Dimension	Outer Diameter36mm Baffle Opening5.0mm Height Refer to drawing in details;
阻抗 Nominal Impedance	8 0hm ± 15% At1000 HZ
额定功率 Power Rating	0.5 watt Maximum 0.7 Watt
最低共振频率 Lowest Resonant Frequency	600 ± 20% HZ.
灵敏度 Output Sound Pressure Level (S. P. L)	90 ± 3db/0.1 Watt. 10CMeter. Average at800, 1000, 1200, 1500HZ.
频率范围 Frequency Range	F0-12 KHZ , Average SPL ± 10db
失真率 Distortion	5%Maximum At1000HZ 0.5 W
极性 Polarity	Diaphragm shall move forward when Apply a Postive DC current the "+" or"Marked" Terminal
寿命测试 Load Test	Bt Audio Singnal Generator At 2.0 Volts. total 48 hours and20~20KHZ Resonant Frequency
异音测试 Abnormal Sound Test	Must be Normally tested Bt 2.0 Volts Sinwave
工作温度 Operation Temperature	= 20℃ ~ ± 50℃
储藏温度 Storage Temperature	= 40℃ ~ ± 60℃

