



**SPECIFICATION**

Contact Rating : 50mA, 12V DC  
 Contact Resistance : 100mΩ max  
 Insulation Resistance : 100mΩ min.500V DC  
 Dielectric Strength : 250V AC/1minute  
 Travel : 0.13mm  
 Operating Temp : -30°C ~ +85°C  
 Storage Temp : -30°C ~ +80°C

PAPT NO	TS-2030-2-X
Operating Force	B: 160gf C: 260gf
Height	H: 0.58

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp		—
②	Cover	—	1	Polyamide	Plating Nickel	—
①	Keystake	—	1	Pet		—

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TACT SWITCH
ΔX					units: mm	DWN	DATE	VIEW:	PART NO.:
ΔX					tolerance:	CHKD	DATE	UNIT: mm	DWG NO.:
ΔX					X.X ±0.2mm	APPD	DATE	SIZE: A4	TS-2030-2-X
					X.XX ±0.1mm	XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
					X.XXX ±0.05mm				1.0g
REVISIONS									SHEET
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn									1/1
									REVISION
									A0