

SCHMATIC

FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 1.5mm to latch.
- Compact spacing on PCB of **13X 8.5mm**.

SPECIFICATIONS


1.ELECTRICAL

● Contact rating	0.1 A, 30VDC
● Contact resistance	50mW Max.
● Insulation resistance	100M W Min. at 250VDC
● Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Operating: +5°C to +55°C Storage: -25°C to +65°C
● Operation force	1.60±80gf
● Stroke	Lock Stroke: 1.5±0.2mm Full Stroke: 2.5±0.2mm
● Operating life	full load: 1 x 10 ⁴ cycles no load: 1 x 10 ⁵ cycles
● Contact form	DPDT

PAPT NO	XKB1385-X
OPERATION	W:NO LOCK Z:LOCK



⑦	Contact	—	4	Phosphor bronze	Plating silvering	—
⑥	Terminal	—	12	Brass	Plating silvering	—
⑤	Spring	—	1	Sus	Natural	—
④	Base	—	1	Nylon		—
③	Crochet Needle	—	1	Sus	Natural	—
②	Cover	—	1	Nylon		—
①	Keystake	—	1	Nylon		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE: KEY SWITCH	
ΔX					X.X	±0.2mm	DWN		DATE		VIEW:	PART NO.:	
ΔX					X.XX	±0.1mm	CHKD		DATE		UNIT: mm	DWG NO.:	
ΔX					X.XXX	±0.05mm	APPD		DATE		SIZE: A4	XKB1385-X	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT 1.0g	SHEET 1/1	REVISION A0