

SCHEMATIC (NON-SHORTING)

FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 2.0mm to latch.
- Compact spacing on PCB of 8.5mm.

SPECIFICATIONS


1.ELECTRICAL

● Contact rating	0.1A, 30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MMin. at 250VDC
● Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Operating: -15°C to +55°C Storage: -25°C to +65°C
● Operation force	160±80gf
● Stroke	Lock Stroke: 2.0±0.2mm Full Stroke: 2.5±0.2mm
● Operating life	full load: 1x10 ⁴ cycles no load: 1x10 ⁵ cycles
● Contact form	DPDT

PAPT NO	XKB8585-X-140
OPERATION	W:NO LOCK Z:LOCK



XKBL SWITCH CONNECTOR

⑦	Contact	—	2	Phosphor bronze	Plating silvering	—
⑥	Terminal	—	6	Brass	Plating silvering	—
⑤	Spring	—	1	Sus	Natural	—
④	Base	—	1	Pbt		—
③	Crochet Needle	—	1	Sus	Natural	—
②	Cover	—	1	Pom		—
①	Keystake	—	1	Pom		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					DSND		DATE		SCALE: N/A	MODEL TYPE: KEY SWITCH	
					ANGLAR		DATE		VIEW:	PART NO.:	
					X.X	±5°	DATE		UNIT: mm	DWG NO.:	
					X.XX	±0.2mm	DATE		SIZE: A4	XKB8585-X-140	
					X.XXX	±0.1mm	DATE			WEIGHT	
					X.XXX	±0.05mm	DATE			1.0g	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO.,LIMITED				SHEET	
REVISIONS										1/1	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn											A0