


额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	100mΩ max.
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.
操作力 Operation force	160±30gf 250±50gf
寿命试验 Operating Life	100,000 cycles 70,000 cycles
行程 Travels	0.15±0.1mm



项目	名称	材质	数量	备注
∩	盖板	不锈钢	1	酸洗
∩	按钮	PPA白	1	
∩	簧片	进口不锈钢复银	1	覆银
+	底座	LCP白	1	镀银
+	卡件	磷铜	1	镀镍银

尺寸范围	±0.05	±0.10	±0.20
0~3	±0.05	±0.10	±0.20
>3~6	±0.05	±0.10	±0.30
>6~30	±0.10	±0.20	±0.50
>30~120	±0.15	±0.30	±0.80

未注尺寸公差 (mm)

第一视角	设计 Jack Jin	图面 单位	A4 MM
	审核 Jacky Zhong	比例 重量	
	批准 Tony Meng	页码 版次	1/1 A/0

东莞市美韩电子科技有限公司 Dongguan Usakro Electronic Technology Co., Ltd.			
1:1	DWG NO.	型号:UK-B0267-ZT-SP25Y	SIZE A4
1 of 1	PART NO.	规格: 3*4 贴片	VER R