



Panel cut-out

SPECIFICATIONS

Max. current/voltage rating with resistive load:
400mA 32VAC - 100 mA 50VDC - 125 mA 125VAC.
INITIAL CONTACT RESISTANCE: 50 mΩ max.
INSULATION RESISTANCE: 1 GΩ min. at 500VDC.
DIELECTRIC STRENGTH: 1,000 VAC rms.
ELECTRICAL LIFE AT FULL LOAD: 500,000 cycles.
PANEL THICKNESS: 1.5 mm (.059) min. - 4 mm (.157) max.
TOTAL TRAVEL: 1.5 mm(.059).
OPERATING FORCE: 2N~5N.
CONTACT BOUNCE: 10 ms.
MECHANICAL LIFE: 1,000,000 cycles.
TORQUE: 0.5 Nm max. applied to nut.
SOLDERING: 350°C max. for 5 seconds.

MATERIALS

CASE: Diallyl phthalate (DAP)(UL94v-0).
CAP: Polyamide 6/6.
BUSHING: Polyamide 6/6.
TERMINAL/CONTACTS: Gold over silver plated.
RoHS & Lead Free

Model No.	POS.1	POS.2
PAS6	OFF	MOM
Term. Comm.	OPEN	SHORT
SCHEMATIC		

SWITCH FUNCTION

	PART NO.	PART NAME	Q'TY
1	MNU- PA03	M12x0.75 SI NUTS	1
2	MNU-1M09	LOCKING WASHER	1
3	FSU- PA01	EVA WASHER	1

FILE NAME:HARDWARE-0011

德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.

符號	原尺寸	修改後尺寸	變更日期	SCALE (比例) : 3 : 2	TITLE 圖名	Sub - Miniature Pushbutton Switches	SIZE 圖紙	A4		
1	(A)			TOLERANCE (公差) : 0.00 mm ± 0.25mm 0.0 mm ± 0.40mm ANGULAR : ± 5° FILE NAME : PASP0509	DWG NO. 圖號	PAS6B2M1CESG3-5	UNIT 單位	inch mm		
2	(B)				REV. 版本	A	DATE 日期	AUG - 11 - 2016	SHEET 張數	1 of 1
3	(C)				CHECKED BY 審核			DRAWN BY 製圖	IRENE	
4	(D)									
5	(E)									