



P. C. B LAND DI MENSION

PAPT NO	TS-3027-X
Operating Force	B:160gf C: 250gf
Height	H: 1.4

**SPECIFICATION**  
 Contact Rating: 50mA,12V DC  
 Contact Resistance: 100mΩ max  
 Insulation Resistance: 100mΩ min.500V DC  
 Dielectric Strength: 250V AC/1minute  
 Travel: 0.12mm  
 Operating Temp: -30°C~+85°C  
 Storage Temp: -30°C~+80°C

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp		—
②	Cover	—	1	Sus	Plating Nickel	—
①	Keystake	—	1	Lcp		—

REVISIONS					units:	mm	DSND	DATE	SCALE: N/A	MODEL TYPE:		
ΔX	DESCRIPTION	DATE	REVISED	APPROVED	tolerance:		DWN	DATE	VIEW:	TACT SWITCH		
ΔX					X.X	±0.2mm	CHKD	DATE	UNIT: mm	PART NO.:		
ΔX					X.XX	±0.1mm	APPD	DATE	SIZE: A4	DWG NO.:		
MARK					X.XXX	±0.05mm				TS-3027-X		
					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn										1.0g	1/1	A0