



| | |
|-----------------|-------------------------|
| PAPT NO | TS-1187B-X |
| Operating Force | A:100gf B:160gf C:260gf |
| Height | H:0.75 |
| | |
| | |

SPECIFICATION

Contact Rating: 50mA,12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min.500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.25mm
 Operating Temp: -30℃~+85℃
 Storage Temp: -30℃~+80℃

SWITCH CONNECTOR

| ITEM | PAPT NAMF | TER,NO | QTY | MATERIAL | FINISHING | REMARK |
|------|-----------|--------|-----|---------------|-------------------|--------|
| ⑤ | Terminal | — | 4 | Brass (0.30t) | Plating silvering | — |
| ④ | Contact | — | 1 | F.ag/Sus | Natural | — |
| ③ | Base | — | 1 | Pa46 | | — |
| ② | Cover | — | 1 | Spcc | Plating Nickel | — |
| ① | Keystake | — | 1 | Pa46 | | — |

| | | | | | | | | | | | | |
|---|-------------|------|---------|----------|---------------|--------------------------------------|--|------|--|------------|----------------------------|----------|
| | | | | | units: mm | DSND | | DATE | | SCALE: N/A | MODEL TYPE: TACT SWITCH | |
| | | | | | tolerance: | DWN | | DATE | | VIEW: | PART NO.: | |
| | | | | | X.X ±0.2mm | CHKD | | DATE | | UNIT: mm | DWG NO.: | |
| | | | | | X.XX ±0.1mm | APPD | | DATE | | SIZE: A4 | TS-1187B-X | |
| | | | | | X.XXX ±0.05mm | KXB INDUSTRIAL PRECISION CO.,LIMITED | | | | WEIGHT | SHEET | REVISION |
| UNSPECIFIED TOLERANCES | | | | | 1.0g | | | | | 1/1 | A0 | |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | | | | | | | | |
| REVISIONS | | | | | | | | | | | | |
| www.xk-dg.cn www.helloxkb.com www.helloxkb.cn | | | | | | | | | | | | |