



技术参数

1. 额定电流: DCV 50mA.
2. 耐电压: 交流250伏 (50-60赫兹) 持续1分钟.
3. 接触阻抗: 100毫欧max.
4. 绝缘阻抗: 100兆欧min 250V DC.
5. 操作力: $450 \text{gf} \pm 100 \text{gf}$.
6. 产品寿命: 100,000次.
7. 导通行程: $1.20 \pm 0.25 \text{mm}$.
8. 操作类型: 触动回复式.

电路图

②	Terminal	3	Phosphor bronze Au Plating
①	Housing	1	Nylon Black
ITEM	PART NAME	TERN.O.	QTY.
APPROVALS		DATE	
DRAWN		J.X.Zhong	2013/11/11
CHECKED			
APPROVALS			
TOLERANCES ARE		30~12.5	± 0.30
		10~30	± 0.20
		5~10	± 0.15
		~5	± 0.10
TITLE:		LED Tact Switch	
PART NO.		K6-6610D	
SCALE:		1:1	
DRAWING NO.			
PROJ:			
SHEET		1 OF 1	

ELECTRONICS CO.,LTD



ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			