



P.C.B. DIMENSION

SPECIFICATION

1. Operating Voltage : 42v
(None-Switching : 400mA)
(Switching : 100mA)
2. Contact Resistance : 80mΩ Max
3. Insulation Resistance : 100MΩ Min
4. Operating Force : 120gf±30gf Max
5. Life cycle : 25,000 steps

		Real Coded				
		C	1	2	4	8
10 P o s i t i o n	0	●				
	1	●	●			
	2	●		●		
	3	●	●	●		
	4	●			●	
	5	●	●			●
	6	●		●		●
	7	●	●	●	●	
	8	●				●
	9	●	●			●
16 P o s i t i o n	A	●		●		●
	B	●	●	●		●
	C	●			●	●
	D	●	●		●	●
	E	●		●	●	●
	F	●	●	●	●	●

△			
△			
△			
△			
△			
SYM	DISCRIPTION	DATE	APPROVED

TACLEX TACLEX ELECTRONICS CO., LTD.				
TOLERANCES UNLESS OTHERWISE SPECIFIED LINEAR: ±0.30 ANGULAR: ±3'		SIGNATURES	DATE	TITLE
		DRAWN Angel	2016.05.10	MINI ROTARY SWITCH
REVISIONS A	SCALE 5/1	CHK'D Jane	2016.05.10	NO.
		APPV'D Rex	2016.05.10	MSDR-16H