

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 10/10/14'	HZW 10/10/14'	LJC 10/10/14'
B	DRAWING UPDATE	JLZ 05/09/16'	HZW 05/09/16'	LJC 05/09/16'



Notes:

- 1.Material:
 - 1.1. Housing: High Temperature LCP UL 94V-0, Color of Black
 - 1.2. Contact: Copper Alloy
 - 1.3. Shell: Stainless Steel
- 2.Finish:
 - 2.1. Contact Area: Gold over Nickel
 - 2.2. Solder Area: Tin.
- 3.Speciality: :
 - 3.1. Current Rating: 1.0A
 - 3.2. Voltage Rating: 30V AC/DC
 - 3.3. Contact Resistance: 100mΩ Max.
 - 3.4. Insulation Resistance: 100MΩ Min.
 - 3.5. Withstanding Voltage: 100V AC.
 - 3.6. Temperature Rated: -40° C TO +105° C,
4. Product Number Code:

DS1138-06 - XX X X X X X X

- XX X X X X X X
- Packing Type
- R: Tape On Reel
- Shell Plating
- S: Stainless
- Housing Color
- B: Black
- Contact Plating
- 4: Selective 3u" gold
- Mounting Type
- S: SMT type
- Connector Type
- S: Socket
- NO. Of Contacts
- 06:6Pin


PIN NO.	PIN NAME
A1	VCC
A2	RST
A3	CLK
A4	Reserved
A5	GND
A6	VPP
A7	I/O
A8	Reserved



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION	TITLE
UNITS	2.54mm SIM Card H=1.8mm 6 Positions SMT Type
SHEET SIZE	A4
SERIES	DS1138-06 SERIES

DRAWING TYPE	CUSTOMER
SCALE	1:1 SHEET 1 OF 1
DRAWING NO.	C-DS1138-06-XXXXXXX-B


晨翔电子有限公司
CONNFLY® CONNFLY ELECTRONIC CO., LTD