SHEET OF



RECOMMENDED P.C.B. LAYOUT





CIRCUIT: DPST

CONTACT CONFIGURATION





NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. ▲ CONTACT MATERIAL: COPPER ALLOY W/ SILVER PLATE
5. RATING: 7A@125V , 4A@250
6. CONTACT RESISTANCE: 20MΩ MAX @ 5V DC 1A
7. DIELECTRIC STRENGTH: AC 1500V RMS
8. OPERATING FORCE: 550±150gf TYP.
9. TRAVEL: FULL:5.5, LOCK:4.0

REV.	ECN No.	DESCRIPTION	DATE	CHKD
D	15234	UPDATED DESCRIPTION	9/2/05	PH
C	11768	REVISED DIMENSION	5/29/02	CB
B	11768	REVISED, AND REDRAWN	10/23/01	CJC

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE: P227 EE 1CXC

SCALE	DATE	DR	DWG	REV
1.5:1	10/23/01	CJC	P030113	D