




GBU10005 THRU GBU1010

GLASS PASSIVATED BRIDGE RECTIFIERS

Reverse Voltage - 50 to 1000 Volts Forward Current - 10.0 Amperes

GBU



Dimensions in inches and (millimeters)

FEATURES

- ◆ Surge overload rating -175 amperes peak
- ◆ Ideal for printed circuit board
- ◆ Reliable low cost construction utilizing molded plastic technique
- ◆ Plastic material has U/L flammability classification 94V-0
- ◆ Mounting position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

MDD Catalog Number	SYMBOLS	GBU 10005	GBU 1001	GBU 1002	GBU 1004	GBU 1006	GBU 1008	GBU 1010	UNITS		
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	VOLTS		
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	VOLTS		
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	VOLTS		
Maximum average forward (with heatsink NOTE 2) Rectified current @ $T_c=100^\circ\text{C}$ (without heatsink)	$I_{(AV)}$	10.0					3.0			Amps	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	220									Amps
Rating for Fusing ($t < 8.3\text{ms}$)	I^2t	200									A^2s
Maximum forward voltage at 5.0A DC	V_F	1.0									Volts
Maximum DC reverse current at rated DC blocking voltage	I_R	$T_A=25^\circ\text{C}$					10				μA
		$T_A=125^\circ\text{C}$					500				μA
Typical Junction Capacitance (Note 1)	C_J	70									pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	2.2									$^\circ\text{C}/\text{W}$
Operating junction temperature range	T_J	-55 to +150									$^\circ\text{C}$
storage temperature range	T_{STG}	-55 to +150									$^\circ\text{C}$

NOTES: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Device mounted on 75mm*75mm*1.6mm cu plate heatsink.

3. The typical data above is for reference only (典型值仅供参考)



RATINGS AND CHARACTERISTIC CURVES GBU10005 THRU GBU1010

FIG.1-MAXIMUM FORWARD SURGE CURRENT




FIG.2- DERATING CURVE
OUTPUT RECTIFIED CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS





FIG.4-TYPICAL REVERSE CHARACTERISTICS



The curve graph is for reference only, can't be the basis for judgment(曲线图仅供参考)!

