



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:—25℃~80℃
 Operating force:3—20N
 Operating Life:5,000cycles

P C B Layout(Top view)

Model NO	PJ-316A-A	PJ-316A-B	PJ-316A-C
Schematic			
Model NO	PJ-316A-D	PJ-316A-E	PJ-316A-F
Schematic			

②	Shunt terminal	6	Phosphor bronze	Plating Au		
①	Housing	1	PPA	Black		
ITEM	PART NAME	Serial number	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				
DRAWN	QIFENG.XU	2014/9/19	ELECTRONICS CO.,LTD			
CHECKED		TITLE:		PHONE JACKETS		
APPROVALS		PART NO.		PJ-316A		
TOLERANCES ARE		30~12.5 ±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:
		10~30 ±0.20		DRAWING NO.		SHEET 1 OF 1
		5~10 ±0.15	±2'			
		~5 ±0.10				

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			